



SINCE 1978

**APEX CONNECTOR**

**APEX** NEW Products

**CONNECTORS**



**錫鋼精密科技股份有限公司**  
**APEX PRECISION TECHNOLOGY CORP.**  
24264 台北縣新莊市民安西路405號 Tel:+886-2-2206-8899 / 2206-7766  
No. 405, Min-an W. Rd., Sinhuang City, Taipei County 24264, Taiwan, R.O.C Fax:+886-2-2208-0559 / 2208-2999  
<http://www.plt.com.tw> <http://ec.plt.com.tw> E-mail:apexmail@plt.com.tw



認明標商、買的安心、優質產品、用的放心



	4	5	6
Contacts Configuration 接點方位			
No. of contacts 接點數目	8	8	7
Rated current / voltage 額定電流 / 電壓	10A 250V	10A 250V	10A 250V
Operation limit voltage (AC.V.rms) 操作電壓限制	300	300	250
Withstanding voltage (AC.V.rms) 1 minute 耐電壓1分鐘	180	180	1000
Insulation resistance (MΩ MIN.) at DC 500V 絕緣阻抗	2000	2000	2000
Contact resistance (mΩ MAX.) at DC 1A 接觸阻抗	3	3	3
Solder inter diameter 焊孔內徑	2.5	2.5	1.6

Contacts Configuration 接點方位
No. of contacts 接點數目
Rated current / voltage 額定電流 / 電壓
Operation limit voltage (AC.V.rms) 操作電壓限制
Withstanding voltage (AC.V.rms) 1 minute 耐電壓1分鐘
Insulation resistance (MΩ MIN.) at DC 500V 絕緣阻抗
Contact resistance (mΩ MAX.) at DC 1A 接觸阻抗
Solder inter diameter 焊孔內徑

接點採用合金材質，彈性極佳、鍍金鍍銀、焊接容易、導電絕佳  
國際驗證通過品質保證

7 PLT-305-P11.6



8 PLT-304-P13.6



9 PLT-304-P11.6



10 PLS-203-PF8



11 PLT-308-RF



12 PLT-304-RM



Contacts Configuration 接點方位

No. of contacts 接點數目

Rated current / voltage 額定電流 / 電壓

Operation limit voltage (AC.V.rms)操作電壓限制


Withstanding voltage (AC.V.rms) 1 minute耐電壓1分鐘

Insulation resistance (MΩ MIN.) at DC 500V 絕緣阻抗

Contact resistance (mΩ MAX.) at DC 1A 接觸阻抗

Solder inter diameter 焊孔內徑

7



5

10A 250V

300


1800

2000

3

2.5

8



4

15A 250V

400


2000

2000

3

2.8

9



4

15A 250V

400


2000

2000

3

2.8

10



3

15A 250V

250


1500

2000

3

1.8

11



8

10A 250V

300


180

2000

3

2.5

12



4

15A 250V

400

2000

2000

3

2.8

Contacts Configuration 接點方位

No. of contacts 接點數目

Rated current / voltage 額定電流 / 電壓

Operation limit voltage (AC.V.rms)操作電壓限制

Withstanding voltage (AC.V.rms) 1 minute耐電壓1分鐘

Insulation resistance (MΩ MIN.) at DC 500V 絕緣阻抗

Contact resistance (mΩ MAX.) at DC 1A 接觸阻抗

Solder inter diameter 焊孔內徑

13 PCT-304K-RM



14 PLS-20-ADCa



15 PLS-207-ADM12



16 PLS-203-ADM8



17 PLT-308-RM



No. of contacts 接點數目
Contacts Configuration 接點方位
Rated current / voltage 額定電流 / 電壓
Operation limit voltage (AC.V.rms) 操作電壓限制
Withstanding voltage (AC.V.rms) 1 minute 耐電壓1分鐘
Insulation resistance (MΩ MIN.) at DC 500V 絕緣阻抗
Contact resistance (mΩ MAX.) at DC 1A 接觸阻抗
Solder inter diameter 焊孔內徑



4
15A 250V
400
2000
2000
3
2.8



7
10A 250V
250
1000
2000
3
1.6



3
15A 250V
400
1500
2000
3
1.8

No. of contacts 接點數目
Contacts Configuration 接點方位
Rated current / voltage 額定電流 / 電壓
Operation limit voltage (AC.V.rms) 操作電壓限制
Withstanding voltage (AC.V.rms) 1 minute 耐電壓1分鐘
Insulation resistance (MΩ MIN.) at DC 500V 絕緣阻抗
Contact resistance (mΩ MAX.) at DC 1A 接觸阻抗
Solder inter diameter 焊孔內徑



8
10A 250V
300
1800
2000
3
2.5

